

EAP111

TIP OPENWIFI ACCESS POINT

INTRODUCTION

EAP111 stands as an enterprise-grade, dual-band Wi-Fi 6 access point boasting a concurrent operation and an IP55-rated enclosure. With support for 2x2:2 uplink and downlink MU-MIMO between the access point and multiple clients, EAP111 delivers an impressive aggregated data rate of up to 3Gbps. Notably, EAP111 comes equipped with a Bluetooth Low Energy (BLE) radio and ZigBee, enabling the integration of value-added applications such as iBeacon.

The TIP OpenWiFi AP EAP111 hardware is pre-installed with TIP's OpenWiFi AP software, saving time and hassle from software installation, but at the same time reserve the flexibility for further changes. From SMB to MDUs to larger venues, the TIP OpenWiFi AP EAP111, with IP55 rating is a flexible hardware platform for various deployment environments.



HIGHLIGHTS

Wi-Fi 6 2x2 uplink and downlink MU-MIMO with up to 3 Gbps data rate

Support up to 32 ESSIDs.

Enterprise-Grade Wireless Security

Bluetooth Low Energy (BLE) and ZigBee support

IP55 rating

SPECIFICATIONS

PHYSICAL	
CPU	MT7981A
Flash	256MB
Memory	512MB
Power	DC Input: 12V / 2.0A (Power adapter not included) PoE: 802.3at compliant (PoE injector not included)
Dimensions	170 mm (L) x 185 mm (W) x 39.45 mm (H)
Weight	0.63 kg
Interfaces	Uplink: 1 x 10/100/1000Base-T Ethernet, Auto MDIX, RJ-45 with 802.3at PoE LAN: 1 x 10/100/1000Base-T Ethernet, Auto MDIX, RJ-45
LED Indicator	1 tri-color LED: Power, Cloud Status, Uplink
Buttons	Restart / Reset
Environmental Conditions	Operating Temperature: 0°C (32°F) to 45°C (113°F) Operating Humidity: 5% to 95% non-condensing IP55 Rating
Power Consumption	21.54W max.
Antenna	Type: Built-in antenna Gain: 4.9 dBi (2.4 GHz), 5.8 dBi (5 GHz), 4 dBi (BLE)
Mounting	Wall/Ceiling/T-bar mount (Mounting kit included), Pole mount (Mount kit & hose clamp optional)
Anti-theft	1 x Kensington lock slot
ESD	IEC-61000-4-2 +/-4KV for contact discharge, +/-8KV for Air discharge (criteria B)
WI-FI	
Standards	802.11a/b/g/n/ac/ax (Wi-Fi 6) Concurrent dual-band 2.4 GHz & 5 GHz
Support Data Rates	802.11b: 1, 2, 5.5, 11 Mbps 802.11a/g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps 802.11n: 6.5 – 300 Mbps (20 / 40 MHz) 802.11ac: 6.5 – 867 Mbps (20 / 40 / 80 MHz) 802.11ax: 3.6 – 574 Mbps (2.4 GHz, 20 / 40 MHz) 802.11ax: 3.6 – 2402 Mbps (5 GHz, 20 / 40 / 80 / 160 MHz)
Radio Chains	2.4 GHz: 2 x 2 5 GHz: 2 x 3
Spatial Streams	2.4 GHz: 2; MU-MIMO support 5 GHz: 2; MU-MIMO support

WI-FI	
Aggregate Conducted Transmit power*¹	2.4 GHz: 25.5dBm* ² 5 GHz: 25dBm* ²
Channelization	2.4 GHz: 20 / 40 MHz 5 GHz: 20 / 40 / 80 / 160 Mhz
Frequency Range	2.401 – 2.483 GHz 5.170 – 5.835 GHz
Operating Channels	2.4 GHz: 1 –11 (US), 1 –13 (Europe), 1 –13 (Japan) 5 GHz* ³ : 36 –165 (US), 36 –140 (Europe), 36 –144 (Japan)
ESSID	Up to 16 per radio (32 total)
Certification	FCC, IC, CE, LVD, TELEC, VCCI, NCC, BSMI

PERFORMANCE	
Physical Data Rate	Up to 574 Mbps (2.4 GHz) Up to 2,400 Mbps (5 GHz)

FIRMWARE	
TIP OpenWiFi Ready	

PART NUMBER	
EAP111 (T)	TBD
131500000316A	Optional power adapter with changeable US / JP / EU / UK plugs
131500000206A	Optional POE29U-560 (30W PSE Injector)
123400001540A	Optional metal pole mount bracket
125900000249A	Optional hose clamp

Contact Us

For more information, please contact us: openwifi@edge-core.com

EC OpenWiFi Page

<https://wifi.edge-core.com/openwifi>

EC OpenWiFi User Forum

<https://community.wifi.edge-core.com/>